

## **Request for Quotation**

### W Pan Patio Covers

**Important:** Throughout the spring and summer seasons our we do quote submissions on a first come first serve basis and work hard to do them right the first time. We believe in honoring our commitment to each customer that requests a quotation, therefore we can not consider demands for immediate quotations. We will generally be able turn quotations in about 2-3 days. During peak season we will require up to 3-4 days to do a quotation.

#### **Basic Information**

	First Name:	Last Name:						
Step 1.	City of Installation:		State:					
	Contact Tel. #	Email Address:						
	(We do not call unless your email address is entered incorrectly)	(We have never sold or exchanged your email addresses or other information with any other company!)						
Loa	d Requirement Information							
Step 2.	Your city building department is where building permits are issued from. You may or may not need an actual permit for your installation, and this is left as the sole responsibility of the homeowner. <a href="It is our strong recommendation that you acquire your permit prior to purchase">It is our strong recommendation that you acquire your permit prior to purchase</a> . However, panel thickness, beam placements, beam size, distance between posts out front all are a function of the load (snow & wind) that your cover will be subject to. Even though you may not require a permit, you will still need to contact them to get your local building code requirements so that we can supply you with the 'correct' materials!  Snow Load (lbs./sq.ft.):  Will you be getting a permit?  Wind Load (mph):  YES  NO							
Step 3.	Our Terminology  Patio Cover Terminology	8 9 -	1. Height 2. Panel Span (beam place) 3. Total Projection 4. Width 5. Post 6. Beam 7. Fascia / Wall	ment)				
	, , , , , , , , , , , , , , , , , , , ,		8. Front Overhang					





9. Distance Between Posts



# **Request for Quotation**

W Pan Patio Covers

### **Patio Cover Details**

	Top Only	C	omplete	Cover	Free Sta	nding			
	(Beam & Posts (Full set of Beam  NOT Included) & Posts Included)				(2 Full Sets of Beam & Posts Included)				
Step 4.	Height on House Wall or Fascia Board: From deck to the underside of roof installation point			Desired Front Overhang:		ft.	in.		
	ft. in.			Amount of awning past the front beam & post assembly. Max overhang is 3' or 25% of awning span - <b>whichever is less.</b>					
	Projection:	ft.		in.	Choose one				
	Total distance <u>away</u> from wall  including overhang past front beam & post assembly.		Posts attached to wood/trex deck						
	Width:	ft.	in.		Posts attache	d to ceme	ent pad		
Total distance <u>parallel</u> to house wall  Posts buried / cemented in ground									
Color Selection					White	Bronze	Clay		
	<b>Roof Panel Color</b>	Selection							
	White	lvory			lv	vory	Gray	Brown	
Step 5.	Fascia Gutter Color Selection								
	White	Bronze		Clay	Ivory	Gray		Brown	
	Beam Color Selection			Post Color Selection					
	White	Bronze			White	Bronze		Ivory	

## **SEND QUOTE REQUEST TO:**



quote@homeporchand patiok its.com



1.705.259.2264